



General Specification :

- Lead Wire: UL Type
(+)Red (-)Black (FG)Yellow
- Operation Temperature :
Temperature: $-10^{\circ}\text{C} \sim +70^{\circ}\text{C}$
Humidity: 35%~85%RH
- Store Temperature :
Temperature: $-40^{\circ}\text{C} \sim +70^{\circ}\text{C}$
Humidity: 35%~85%RH

Motor Protection :

- Impedance Protected
- Reverse Polarity Protected

| Item No. | Bearing System | Rated Voltage (V DC) | Rated Current (AMP) | Input Power (Watt) | Fan Speed (RPM) | Air Flow (CFM) | Static Pressure (MM-H2O) | Noise Level (dBA) | Dimension (mm) |
|------------------------|----------------|----------------------|---------------------|--------------------|-----------------|----------------|--------------------------|-------------------|----------------|
| BF7525L12S (Frameless) | Sleeve | 12V | 0.20 | 2.40 | 2,100± 10% | --- | --- | 27 | Φ74 x 25 |
| BF7525M12S (Frameless) | Sleeve | 12V | 0.25 | 3.00 | 2,500± 10% | --- | --- | 32 | Φ74 x 25 |
| BF7525H12S (Frameless) | Sleeve | 12V | 0.35 | 4.20 | 3,500 ± 10% | --- | --- | 41 | Φ74 x 25 |